



Cable ID: P8-071-4 1/7#

Test Limit: ISO Patch Cord Cat6A 1.0m

Limits Version: V7.7

Date / Time: 02/02/2023 09:19:42 AM

Headroom 2.7 dB (NEXT 3,6-4,5)

Cable Type: Cat 6A U/UTP

NVP: 68.2%

Main: Versiv

S/N: 1707014

Software Version: V6.8 Build 6

Calibration Date: 02/23/2022

Adapter: DSX-8000 (DSX-PC6A)

S/N: 3661383

Test Summary: PASS

Remote: Versiv

S/N: 1707027


Software Version: V6.8 Build 6

Calibration Date: 02/23/2022


Adapter: DSX-8000R (DSX-PC6A)

S/N: 3661361

Length (ft)	[Pair 1,2]	4
Prop. Delay (ns)	[Pair 3,6]	6
Delay Skew (ns)	[Pair 1,2]	0
Resistance (ohms)	[Pair 3,6]	0.23



Wire Map (T568B)



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	3,6-4,5
NEXT (dB)	2.8	2.7	4.6	3.7
Freq. (MHz)	241.0	241.0	431.0	432.0
Limit (dB)	39.5	39.5	32.7	32.7

PASS	MAIN	SR	MAIN	SR
Worst Pair	3,6	3,6	3,6	3,6
RL (dB)	0.6	1.2	0.6	2.3
Freq. (MHz)	353.0	275.0	353.0	446.0
Limit (dB)	11.8	13.4	11.8	10.2

