



Cable ID: P8-005-24 TEST-2


Test Limit: TIA Patch Cord Cat6 1.0m
Limits Version: V7.7
Date / Time: 03/28/2023 10:18:07 AM
Headroom 3.8 dB (NEXT 3,6-4,5)
Cable Type: Cat 6 F/UTP
NVP: 70.0%

Main: Versiv
S/N: 1707014
Software Version: V6.8 Build 6
Calibration Date: 02/23/2022
Adapter: DSX-8000 (DSX-PC6)
S/N: 3544526


Test Summary: PASS

Remote: Versiv
S/N: 1707027
Software Version: V6.8 Build 6
Calibration Date: 02/23/2022
Adapter: DSX-8000R (DSX-PC6)
S/N: 3549014

Length (ft)	[Pair 1,2]	4
Prop. Delay (ns)	[Pair 3,6]	6
Delay Skew (ns)	[Pair 1,2]	0
Resistance (ohms)	[Pair 4,5]	0.24



Wire Map (T568B)



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	1,2-3,6
NEXT (dB)	3.8	4.2	4.1	5.3
Freq. (MHz)	206.0	211.0	211.5	242.5
Limit (dB)	40.9	40.7	40.6	39.5

PASS	MAIN	SR	MAIN	SR
Worst Pair	1,2	1,2	4,5	4,5
RL (dB)	5.9	7.2	7.7	7.5
Freq. (MHz)	34.3	33.8	211.0	206.0
Limit (dB)	22.6	22.7	14.7	14.8

