

Cable ID	Summary	Test Limit	Length	Headroom	Date / Time
C6A-UTP-P8-063-9-1M-10	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	2.3 dB (NEXT)	01/06/2016 04:14 PM
C6A-UTP-P8-063-9-1M-09	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	1.3 dB (NEXT)	01/06/2016 04:14 PM
C6A-UTP-P8-063-9-1M-08	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	2.2 dB (NEXT)	01/06/2016 04:13 PM
C6A-UTP-P8-063-9-1M-07	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	2.4 dB (NEXT)	01/06/2016 04:12 PM
C6A-UTP-P8-063-9-1M-06	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	2.5 dB (NEXT)	01/06/2016 04:11 PM
C6A-UTP-P8-063-9-1M-05	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	2.1 dB (NEXT)	01/06/2016 04:11 PM
C6A-UTP-P8-063-9-1M-04	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	2.1 dB (NEXT)	01/06/2016 04:10 PM
C6A-UTP-P8-063-9-1M-03	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	2.1 dB (NEXT)	01/06/2016 04:10 PM
C6A-UTP-P8-063-9-1M-02	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	2.8 dB (NEXT)	01/06/2016 04:08 PM
C6A-UTP-P8-063-9-1M-01	PASS	ISO Patch Cord Cat6A 1.0m	3 ft	1.7 dB (NEXT)	01/06/2016 04:04 PM

Total Length:	30 ft
Number of Reports:	10
Number of Passing Reports:	10
Number of Failing Reports:	0
Number of Warning Reports:	0
Documentation Only:	0



Cable ID: C6A-UTP-P8-063-9-1M-10

Date / Time: 01/06/2016 04:14:35 PM

Headroom **2.3 dB (NEXT 36-45)**

Test Limit: **ISO Patch Cord Cat6A 1.0m**

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.1





Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.3		3.1	
Freq. (MHz)	328.0		432.0	
Limit (dB)	36.0		32.7	

PASS	MAIN	SR	MAIN	SR
Worst Pair	45		78	
RL (dB)	6.0		6.0	
Freq. (MHz)	371.0		454.0	
Limit (dB)	11.4		10.1	





Cable ID: C6A-UTP-P8-063-9-1M-09

Date / Time: 01/06/2016 04:14:03 PM

Headroom 1.3 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 1.0m

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 45]	0.1





Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	1.3		1.3	
Freq. (MHz)	336.0		439.0	
Limit (dB)	35.7		32.5	

PASS	MAIN	SR	MAIN	SR
Worst Pair	12		12	
RL (dB)	4.9		4.9	
Freq. (MHz)	463.0		463.0	
Limit (dB)	10.0		10.0	





Cable ID: C6A-UTP-P8-063-9-1M-08

Date / Time: 01/06/2016 04:13:34 PM

Headroom 2.2 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 1.0m

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.1





Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.2		2.2	
Freq. (MHz)	440.0		440.0	
Limit (dB)	32.5		32.5	

PASS	MAIN	SR	MAIN	SR
Worst Pair	78		78	
RL (dB)	4.3		4.3	
Freq. (MHz)	455.0		459.0	
Limit (dB)	10.1		10.0	





Cable ID: C6A-UTP-P8-063-9-1M-07

Date / Time: 01/06/2016 04:12:23 PM

Headroom 2.4 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 1.0m

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.0





Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.4		2.4	
Freq. (MHz)	440.0		443.0	
Limit (dB)	32.5		32.4	

PASS	MAIN	SR	MAIN	SR
Worst Pair	45		45	
RL (dB)	4.8		4.8	
Freq. (MHz)	373.0		373.0	
Limit (dB)	11.4		11.4	





Cable ID: C6A-UTP-P8-063-9-1M-06

Date / Time: 01/06/2016 04:11:49 PM

Headroom 2.5 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 1.0m

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.0





Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.5		2.5	
Freq. (MHz)	333.0		440.0	
Limit (dB)	35.8		32.5	

PASS	MAIN	SR	MAIN	SR
Worst Pair	45		78	
RL (dB)	5.1		5.7	
Freq. (MHz)	358.0		465.0	
Limit (dB)	11.7		10.0	





Cable ID: C6A-UTP-P8-063-9-1M-05

Date / Time: 01/06/2016 04:11:22 PM

Headroom 2.1 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 1.0m

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.0





Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.1		2.1	
Freq. (MHz)	436.0		436.0	
Limit (dB)	32.6		32.6	

PASS	MAIN	SR	MAIN	SR
Worst Pair	36		78	
RL (dB)	5.4		5.7	
Freq. (MHz)	326.0		463.0	
Limit (dB)	12.3		10.0	





Cable ID: C6A-UTP-P8-063-9-1M-04

Date / Time: 01/06/2016 04:10:38 PM

Headroom 2.1 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 1.0m

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.1





Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.1		2.1	
Freq. (MHz)	331.0		437.0	
Limit (dB)	35.9		32.6	

PASS	MAIN	SR	MAIN	SR
Worst Pair	36		36	
RL (dB)	5.1		5.1	
Freq. (MHz)	422.0		422.0	
Limit (dB)	10.6		10.6	





Cable ID: C6A-UTP-P8-063-9-1M-03

Date / Time: 01/06/2016 04:10:10 PM

Headroom 2.1 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 1.0m

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.1





Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.1		2.6	
Freq. (MHz)	333.0		435.0	
Limit (dB)	35.8		32.6	

PASS	MAIN	SR	MAIN	SR
Worst Pair	12		12	
RL (dB)	4.6		4.6	
Freq. (MHz)	456.0		463.0	
Limit (dB)	10.1		10.0	





Cable ID: C6A-UTP-P8-063-9-1M-02

Date / Time: 01/06/2016 04:08:55 PM

Headroom **2.8 dB (NEXT 36-45)**

Test Limit: **ISO Patch Cord Cat6A 1.0m**

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.1





Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.8		2.8	
Freq. (MHz)	338.0		444.0	
Limit (dB)	35.6		32.4	

PASS	MAIN	SR	MAIN	SR
Worst Pair	45		45	
RL (dB)	4.9		4.9	
Freq. (MHz)	370.0		370.0	
Limit (dB)	11.4		11.4	





Cable ID: C6A-UTP-P8-063-9-1M-01

Date / Time: 01/06/2016 04:04:47 PM

Headroom 1.7 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 1.0m

Cable Type: Cat 6A U/UTP

Calibration Date: 05/18/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 68.2%

Test Summary: PASS

Model: DTX-1800


Main S/N: 9634163

Remote S/N: 9659098


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	3
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.1



Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	1.7		1.7	
Freq. (MHz)	440.0		445.0	
Limit (dB)	32.5		32.3	

PASS	MAIN	SR	MAIN	SR
Worst Pair	78		78	
RL (dB)	4.5		4.5	
Freq. (MHz)	453.0		459.0	
Limit (dB)	10.1		10.0	

