



Cable ID: P8-064-5 C6A 1M-1


Date / Time: 02/03/2017 01:04:20 PM
Headroom 3.4 dB (NEXT 36-45)
Test Limit: ISO Patch Cord Cat6A 1.0m
 Cable Type: Cat 6A F/UTP
 NVP: 74.0%

Operator: Your Name
 Software Version: 2.7700
 Limits Version: 1.9400
 Calibration Date:
 Main (Tester): 03/25/2015
 Remote (Tester): 03/25/2015


Test Summary: PASS

Model: DTX-1800
 Main S/N: 8943015
 Remote S/N: 8943016
 Main Adapter: DTX-PC6A/MN ISO/IEC
 Remote Adapter: DTX-PC6A/SR ISO/IEC


Length (ft)	[Pair 12]	4
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.0



Wire Map (T568B)
PASS



	Worst Case Margin		Worst Case Value	
PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-78	
NEXT (dB)	3.4		5.2	
Freq. (MHz)	333.0		500.0	
Limit (dB)	35.8		31.0	



PASS	MAIN	SR	MAIN	SR
Worst Pair	12		78	
RL (dB)	3.3		5.2	
Freq. (MHz)	25.1		478.0	
Limit (dB)	24.0		9.8	

