

Plug Master Industrial Co., Ltd

ENGINEERING DEPT.	PRODUCT SPECIFICATION For P6 Series Telephone plug and network plug technical specification	ReportNo.: HC20051C/2007 Page:1 of 3
--	--	---

1 · SCOPE:

The test tested according to the standard foundation, tested aspect and obeyed allied editor request.

2 · APPLICABLE STANDARDS :

EIA-364-23B Electrical Connector Tests

3. APPLICABLE SERIES NO.:

PMC No. P6-001,P6-002, P6-003, P6-004, P6-005, P6-006

6P6C, 6P4C,6P2C Modular Plug

4. SHAPE,CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS:

Housing: Polycarbonate 94V2s 、 94V0s(UL NO:E205572)NO Poison

Contact: high and strong standard material of the power copper metal alloy

JIS C5191 Rs-Hs(PBR-2)

6. TEST ENVIRONMENT:

Test and measurements shall be conducted under
the below ambient conditions:

Room temperature: $25\pm 2^{\circ}\text{C}$

Room humidity: $55\pm 5\%$

Plug Master Industrial Co., Ltd

ENGINEERING DEPT.	PRODUCT SPECIFICATION For P6 Series Telephone plug and network plug technical specification	ReportNo.: HC20051C/2007 Page:2 of 3
--	--	---

7. ELECTRICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
7.1	Withstand Voltage	Apply 1000V AC for 1 minute between adjacent terminal	No breakdown
7.2	Rated current and voltage	Operation temperature:-40~+125°C Suitable Wiring:AWG24-26	1.5A 125V AC(r.m.s.)
7.3	Contact Resistance	Dry circuit of DC 20mV MAX, 100mA MAX	20MΩ MAX
7.4	Insulation Resistance	Apply 500V DC for 1 minute between adjacent terminal	500MΩ MIN

8.MECHANICAL PERFORMANCE

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Insert Force	Insert applicable jack at a rate of 10mm/second	20N MAX
8.2	Retention Force	Pull out applicable plug at a rate of 10mm/ second	75.46N MIN
8.3	Durability	Strike handle 1000times at a rate of 30 times/minute	No rupture、 No crack

Plug Master Industrial Co.,Ltd

ENGINEERING DEPT.	PRODUCT SPECIFICATION For P6 Series Telephone plug and network plug technical specification	ReportNo.: HC20051C/2007 Page3 of 3
--	--	--

9.ENVIRONMENTAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Salt Spray	Temperature: $35 \pm 3^{\circ}\text{C}$ Salt Solution Density: $5 \pm 1\%$ Duration: 48 ± 4 hours Measurement must be take after Water rinse	Contact resistance: 20 MΩ MAX
9.2	Vibration	1.5mm 10-55-10HZ/minute each 2 hours for X,Y and Z directions	Appearance: No damage Discontinuity: 1 micro second MAX
9.3	Heat aging	$96 \pm 2^{\circ}\text{C}$ for 96 hours	Contact resistance: 20 MΩ MAX
9.4	Humidity	$40 \pm 2^{\circ}\text{C}$,90~95% RH,96 hours	Contact resistance: 30 MΩ MAX
9.5	Thermal Shock Test	$-25 \pm 3^{\circ}\text{C}$ for 30 minute $+95 \pm 3^{\circ}\text{C}$ for 30 minute on Continuous for 25 cycles	Contact resistance: 20 MΩ MAX Insulation resistance: 500 MΩ MIN Withstand Voltage: 1000V AC/Minute

APPROVE Jason Yu	CHECK Tina Lin	TEST ZhaoQingFeng
----------------------------	--------------------------	-----------------------------