

Cable ID: G10BA1SIX CABLE P8-029-5 STR 2M

Test Limit: ISO Patch Cord Cat6A 2.0m

Limits Version: V7.6

Date / Time: 08/18/2022 02:33:46 PM

Headroom 0.9 dB (NEXT 3,6-4,5)

Cable Type: Cat 6A U/UTP

NVP: 68.2%

Main: Versiv

S/N: 1707014

Software Version: V6.7 Build 1

Calibration Date: 02/23/2022

Adapter: DSX-8000 (DSX-PC6A)

S/N: 3661361

Test Summary: Acceptable

Remote: Versiv

S/N: 1707027


Software Version: V6.7 Build 1

Calibration Date: 02/23/2022


Adapter: DSX-8000R (DSX-PC6A)

S/N: 3661383

Length (ft)	[Pair 1,2]	7
Prop. Delay (ns)	[Pair 3,6]	12
Delay Skew (ns)	[Pair 3,6]	1
Resistance (ohms)	[Pair 3,6]	0.48



Wire Map (T568B)



Worst Case Margin Worst Case Value

Acceptable	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	3,6-4,5
NEXT (dB)	0.9	1.2	1.0	1.3
Freq. (MHz)	485.0	485.0	486.0	487.0
Limit (dB)	31.4	31.4	31.3	31.3

PASS	MAIN	SR	MAIN	SR
Worst Pair	4,5	4,5	4,5	4,5
RL (dB)	3.3	2.0	3.3	2.0
Freq. (MHz)	487.0	487.0	487.0	487.0
Limit (dB)	9.7	9.7	9.7	9.7

