


Drawing Number: P8-031-□□□□□

- Housing Material: Polycarbonate, UL Flammability Rating:
 - ①=UL 94V-0, RoHS Compliant.
 - ②=UL 94V-2, RoHS Compliant.
- Contacts Type:
 - ①=Straight pin fits Stranded wire only.
 - ②=Two prong angled pin fits Solid/Stranded Wires.
 - ③=Three prong pin fits Solid/Stranded Wires.
- Gold Plating:
 - Ⓕ= Fu" (Flash), Ⓐ=2-3u" (0.0508 μm ≤ A ≤ 0.0762 μm),
 - Ⓜ= 3u" (≥ 0.0762 μm), Ⓡ= 6u" (≥ 0.1524 μm),
 - Ⓒ=15u" (≥ 0.381 μm), Ⓣ=30u" (≥ 0.762 μm),
 - ⓔ=50u" (≥ 1.27 μm).
- Packaging Quantity:
 - Ⓢ=1000pcs, Ⓣ=500pcs, Ⓤ=250pcs, Ⓟ=200pcs
 - Ⓡ= 100pcs, Ⓧ= 50pcs, Ⓨ= 25pcs, Ⓩ= 10pcs
 - Ⓤ= Other
- Housing Color: Transparent, other colors are available.
(Red=RD, Orange=OR, Yellow=YL, Green=GN, Blue=BL, Purple=PU, Black=BK)
- Shielded Material: Brass with nickel plated, or Non-Shielded.
- Operating Temperature: -10°C to 60°C.

NO: PX-0XX-□□□□□

- Housing Material (0, 2)
- Contacts type (1, 2, 3)
- Gold plating (F, A, H, B, C, D, E)
- Packaging Quantity (S, T, U, V, W, X, Y, Z)
- Housing Color (RD, OR, YL, GN, BL, PU, BK)



NOTE TOL: ±0.1

B	2018.04.18. Rescheduling coding	3RD		Drawing	<i>Chidy</i>	Date	2004/11/11	UL Code	8P8C-S1
A	An initial version	Unit	m/m	Checked	<i>Chris</i>	Date	2004/11/11	Description	
Rev	Description	Scale	1:1	Approved	<i>Jason</i>	Date	2004/11/11	2 Layers w/Bevel Insert 1.0mm, Shielded	



Plug Master
INDUSTRIAL CO., LTD
www.plugmaster.com.tw