



**Cable ID: C6A S/FTP-1M-2**


Date / Time: 2012/09/27 10:47:39  
 Headroom 2.9 dB (NEXT 36-45)  
 Test Limit: ISO Patch Cord Cat6A 1.0m  
 Cable Type: Cat 7 SSTP  
 Calibration Date: 2012/07/24

Operator: INT-F-12  
 Software Version: 2.6300  
 Limits Version: 1.8100  
 NVP: 76.0%


**Test Summary: PASS**

Model: DTX-1800  
 Main S/N: 1413307  
 Remote S/N: 1413308  
 Main Adapter: DTX-PC6A/MN ISO/IEC  
 Remote Adapter: DTX-PC6A/MN ISO/IEC

Length (m)	[Pair 12]	0.9
Prop. Delay (ns)	[Pair 12]	4
Delay Skew (ns)	[Pair 12]	0
Resistance (ohms)	[Pair 45]	0.3



Wire Map (T568B)



	Worst Case Margin		Worst Case Value	
<b>PASS</b>	MAIN	SR	MAIN	SR
Worst Pair	36-45	36-78		
<b>NEXT (dB)</b>	2.9	3.7		
Freq. (MHz)	294.0	500.0		
Limit (dB)	37.3	31.0		

	Worst Case Margin		Worst Case Value	
<b>PASS</b>	MAIN	SR	MAIN	SR
Worst Pair	36	12		
<b>RL (dB)</b>	1.9	7.3		
Freq. (MHz)	36.3	500.0		
Limit (dB)	22.4	9.5		

