



Cable ID: P8-M15


Date / Time: 06/20/2014 05:29:28 PM
Headroom 3.3 dB (NEXT 36-45)
Test Limit: ISO Patch Cord Cat6A 1.0m
 Cable Type: Cat 6A UTP
 Calibration Date: 03/26/2013

Operator: Your Name
 Software Version: 2.7400
 Limits Version: 1.9300
 NVP: 68.2%


Test Summary: PASS

Model: DTX-1800
 Main S/N: 8943015
 Remote S/N: 8943016
 Main Adapter: DTX-PC6A/MN ISO/IEC
 Remote Adapter: DTX-PC6A/SR ISO/IEC

| | | |
|-------------------|-----------|-----|
| Length (ft) | [Pair 12] | 3 |
| Prop. Delay (ns) | [Pair 36] | 6 |
| Delay Skew (ns) | [Pair 36] | 1 |
| Resistance (ohms) | [Pair 12] | 0.0 |



Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

| PASS | MAIN | SR | MAIN | SR |
|------------------|-------|-------|------|----|
| Worst Pair | 36-45 | 45-78 | | |
| NEXT (dB) | 3.3 | 4.9 | | |
| Freq. (MHz) | 227.0 | 496.0 | | |
| Limit (dB) | 40.0 | 31.0 | | |

| PASS | MAIN | SR | MAIN | SR |
|----------------|-------|-------|------|----|
| Worst Pair | 78 | 78 | | |
| RL (dB) | 3.9 | 3.9 | | |
| Freq. (MHz) | 494.0 | 498.0 | | |
| Limit (dB) | 9.6 | 9.5 | | |

