


Drawing Number: P8-S58-3-□□□□□

1. Housing Material: Polycarbonate, UL Flammability Rating:
 - ①=UL 94V-0, RoHS Compliant.
 - ②=UL 94V-2, RoHS Compliant.
2. Contacts Type:
 - ①=Straight pin fits Stranded wire only.
 - ②=Two prong angled pin fits Solid/Stranded Wires.
 - ③=Three prong pin fits Solid/Stranded Wires.
3. Gold Plating:
 - ⓕ= Fu" (Flash), ⓐ=2-3u" (0.0508 μm ≤ A ≤ 0.0762 μm),
 - ⓗ= 3u" (≥ 0.0762 μm), ⓑ= 6u" (≥ 0.1524 μm),
 - ⓒ=15u" (≥ 0.381 μm), ⓓ=30u" (≥ 0.762 μm),
 - ⓔ=50u" (≥ 1.27 μm).
4. Packaging Quantity:
 - Ⓢ=1000pcs, Ⓣ=500pcs, Ⓤ=250pcs, Ⓥ=200pcs
 - Ⓦ= 100pcs, Ⓧ= 50pcs, Ⓨ= 25pcs, Ⓩ= 10pcs
 - ⓐ= Other
5. Housing Color: Transparent, other colors are available.
(Red=RD, Orange=OR, Yellow=YL, Green=GN, Blue=BL, Purple=PU, Black=BK)
6. Shielded Material: Brass with nickel plated, or Non-Shielded.
7. Operating Temperature: -10°C to 60°C.

— Housing Material (0, 2)
 — Contacts type (1, 2, 3)
 — Gold plating (F, A, H, B, C, D, E)
 — Packaging Quantity (S, T, U, V, W, X, Y, Z)
 — Housing Color (RD, OR, YL, GN, BL, PU, BK)

NO: PX-0XX-□□□□□



NOTE TOL: ±0.1

B	2018.09.07. Rescheduling coding	3RD		Drawing	Chidy	Date	2005/07/23	UL Code	S8P8C-1
A	An initial version	Unit	m/m	Checked	Chris	Date	2005/07/23	Description	
Rev	Description	Scale	1:1	Approved	Jason	Date	2005/07/23	F-L with insert 0.6mm	



Plug Master
INDUSTRIAL CO., LTD
www.plugmaster.com.tw